



2016 Catalogue





Winpact Chiller

The Winpact Chiller series is Major Science's newest addition to the bioprocessing technology portfolio to provide precise temperature control and excellent cooling performance for your fermentation needs and beyond. The recirculating chillers are compactly designed and require very little space; the built-on wheels offer an added bonus of mobility to any space-conscious labs. With a low procurement cost, it is your best option to stray away from costly tap water and is the perfect alternative for basic cooling needs.



CE

WCC-100 / 101

Features

- Compact design
- Overheat protection
- LED display with PID control of 0.1°C resolution
- Self-diagnosed abnormality function
- Delayed resume compressor protection
- Jetstream forced-flow circulation



Digital controller for easy operation

Specification

Cat. No.	WCC-100	WCC-101
Display	LED Display	
Temperature control range	0°C to +100°C	
Temperature stability	± 0.5°C at 20°C	
Temperature accuracy	± 0.5°C at 20°C	
Controller	PID control, PT100 sensor	
Setting / display resolution	± 0.1°C	
Cooling capacity (Medium Ethanol)	1900 BTU/h @ 0°C	
Pump capacity flow rate (L/min)	5.5 L/min	
Hydraulic head	2.5 meter	
Pump capacity flow pressure (bar)	0.19 bar	
Pump connections	1/4" silicone tubing	
Barbed fittings diameter (inner dia. / mm)	6.35 mm or 1/4"	
Bath capacity	10 L	
Refrigerant	CFC free refrigerants-R134a	
Operating temperature	+20°C~+40°C	
Operating humidity	Max.80%	
Rated voltage	110V; 60Hz, 14.5A	220V; 50Hz, 8A
Chamber material	304 stainless steel	
Bath inner dimension	(W x L x H) 9.25"x11.61"x5.90" (235x295x150 mm)	
External material	Powder coating	
Compressor	1/4 HP	
Dimension	(W x L x H) 13.39"x22.04"x26.38" (340x560x670 mm)	
Weight	Approx. 110.2 lb (50 kg)	
Safety device	■ Self-diagnosed abnormality display ■ Electronic overheating thermal fuse protection in increments of 0.1°C ■ Delayed resume compressor protection	
Circulation volume	Cycles up to 5.5 L/min cooling system with delayed resume protection after power outage	
Circulation type	Jet stream flow forced circulation, can be accessed through the outer loop	
Power	1000W	

Ordering Information

Cat. No.	Product Description
WCC-100	Winpact Chiller, 110V
WCC-101	Winpact Chiller, 220V





US Office

19959 Sea Gull Way
Saratoga, CA 95070
U.S.A.
T/ +1-408-366-9866
F/ +1-408-446-1107

Taiwan Office

No. 37, Wuquan 5th Road,
Wugu Dist., New Taipei City 24888
Taiwan
T/ +886-2-2298-1055
F/ +886-2-2299-7871

India Office

No.12-13-104, St. No.3, Lane No.1,
Tarnaka, Secunderabad - 500017
Telengana, India
T/ +91-40-27001515
F/ +91-40-27001515



www.majorsci.com
info@majorsci.com